



Ligao Mechanical Bearing Co., Ltd



207 Bearing 2D drawings and 3D CAD models

Low Price Bearing Housing Unit UC 207 UCP 206 Ucf 205 Ucf 203 Pillow Block Bearings for Trucks

Bearing No. 207

Size	72x35x17 mm
Bore Diameter	72 mm
Outer Diameter	35 mm
Width	17 mm
d	35 mm
D	72 mm
B	17 mm
d ₁	46.94 mm
D ₂	62.69 mm
r _{1,2} - min.	1.1 mm
d _a - min.	42 mm
D _a - max.	65 mm
r _a - max.	1 mm
Basic dynamic load rating - C	27.5 kN
Basic static load rating - C ₀	22 kN
Fatigue load limit - P _u	0.93 kN
Reference speed	17000 r/min
Limiting speed	10000 r/min
Calculation factor - k _r	0.04
Category	Single Row Ball Bearings
Inventory	6.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A



Ligao Mechanical Bearing Co., Ltd

Weight / Kilogram	0.316
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	Yes
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch - Metric	Metric
Long Description	35MM Bore; 72MM Outside Diameter; 17MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; Yes Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	207
Weight / LBS	0.7
Outside Diameter	2.835 Inch 72 Millimeter
Bore	1.378 Inch 35 Millimeter
Outer Race Width	0.669 Inch 17 Millimeter
bore diameter:	35 mm
static load capacity:	22 kN
outside diameter:	72 mm
precision rating:	ABEC 3 (ISO Class 6)



Ligao Mechanical Bearing Co., Ltd

overall width:	17 mm
finish/coating:	Uncoated
bore type:	Round
cage material:	Steel
closure type:	Open
outer ring width:	17 mm
row type & fill slot:	Single Row Filling Slot
fillet radius:	1 mm
snap ring included:	Without Snap Ring
maximum rpm:	10000 RPM
internal clearance:	C0
series:	20
dynamic load capacity:	27.5 kN
thrust application warning:	This product can not be used in Thrust Applications
d_1	46.94 mm
D_2	62.69 mm
$r_{1,2}$ min.	1.1 mm
d_a min.	42 mm
D_a max.	65 mm
r_a max.	1 mm
Basic dynamic load rating C	27.5 kN
Basic static load rating C_0	22 kN
Fatigue load limit P_u	0.93 kN
Calculation factor k_r	0.04
Mass bearing	0.31 kg